

150W, Rugged DC/DC Converter for Railway and other Demanding Environments

DCW 150R Series

- ◆ Field-proven rugged design
- ◆ For train and mobile applications
- ◆ Conduction/convection cooled
- ◆ Full electronic protection
- ◆ Wide selection of input/output combinations



The DCW 150R Series rugged, railway quality DC/DC converter uses a field proven topology to generate up to 150W continuous output power. It is a mature design with a track record in numerous applications. Cooling is via base plate to a heat-sinking surface and by natural convection. Ruggedizing and conformal coating provide added immunity to shock, vibration and humidity. Full electronic protection, low component count, large design headrooms, and the use of components with established reliability result in a high MTBF. The unit meets the requirements of EN 50155 for electronic equipment used on railway rolling stock. It is manufactured at our plant under strict quality control.

SPECIFICATIONS

Input Voltage

48Vdc (29 - 67V)
72Vdc (43 - 101V)
96Vdc (58 - 135V)
110Vdc (66 - 154V)
Other inputs upon request

Input Protection

Inrush current limiting
Varistor
Reverse polarity protection
Internal safety fuse
Lower voltage than the specified minimum input will not damage the unit

Isolation

1500Vdc input to chassis
3000Vdc input to output
1500Vdc output to chassis

Standards

Designed to meet IEC60950 and EN50155

Immunity

Meets criteria of EN50155 and EN50121-3-2 including:
EN 61000-4-2 (ESD)
EN 61000-4-3 (RF Immunity)
EN 61000-4-4 (Fast Transients)
EN 50155 (Surge)
EN 61000-4-6 (Conducted Imm.)
EN 50155 (Voltage Variations)

EMI

EN55022 Class B and EN50121-3-2 conducted and radiated

Switching Frequency

47KHz +/- 2KHz

Output Voltage/Current

12V/12A, 24V/6A, 48V/3A or 110A/1.3A are standard. Derating may be required depending on input voltage Consult factory for other voltages and higher power rating

Redundancy diode

None
Available as option

Line/Load Regulation

+/-1% combined from no load to full load

Dynamic Response

Max 5% voltage deviation for 10% to 50% load step, with better than 1msec recovery time

Output Ripple/Noise

Better than 1% of output voltage peak to peak or 0.2% RMS of the output voltage (20MHZ BW)

Overload Protection

Current limiting with hiccup type short circuit protection
Thermal shut-down with automatic recovery in case of insufficient cooling.

Output Overvoltage Protection

Double regulator loop and transzorb.

Efficiency

80 to 90% at full load depending on input/output configuration

Operating Temperature

-25 to +70oC cold-plate temperature range for full specification

Temperature Drift

0.03% per oC over operating temperature range

Cooling

Conduction to customer heatsink or chassis and natural convection

Environmental Protection

Heavy ruggedizing
Conformal coating

Shock/Vibration

IEC 61373 Cat 1 A&B

Humidity

5 - 95% non-condensing

MTBF

Min. 150,000 hours @ 45°C
Demonstrated MTBF is significantly higher.

Indicators

Green output ON LED visible through cooling slots

Control Input

None

Alarm Output

None
Available as option

Package/Dimensions (W x H x L)

F1: 114 x 51 x 201 mm (4.5" x 2" x 7.9") including terminal block and flanges.
Mounting holes are clear

Weight

0.8kg (1.8 lbs)

Connections

9-pole barrier-type terminal block, 3/8" spacing

RoHS

Fully compliant

Warranty

Two years subject to application within good engineering practice

Terminal Block Pin-out.

OUTPUT						INPUT		
Not Used	-	+	Not Used	Not Used	Not Used	GND	+	-
1	2	3	4	5	6	7	8	9

Enhancements to these general specifications and customizing can be accommodated upon request. Specifications are subject to change.



ANALYTIC SYSTEMS
Power Conversion Solutions

8128 River Way, Delta B.C. V4G 1K5 Canada T. 604.946.9981 F. 604.946.9983 TF. 1.800.668.3884 (US/CANADA)

www.analyticssystem.com