

500W, Encapsulated DC/DC Converter for Railway and other Heavy Duty Environments

RWY 500 Series

- ♦ Rugged, field-proven design
- ♦ Full encapsulation
- ♦ Wide temperature range
- ♦ Full electronic protection
- ♦ EN50155 input ranges



This fully encapsulated, railway quality DC/DC converter uses a field-proven design to generate 500W output power. It is a mature product with a track-record in numerous applications. This converter is entirely potted with a thermally conductive MIL-grade silicon rubber compound to ensure immunity to shock, vibration and humidity. It is conduction cooled via a base plate to a heatsinking surface. Low component count, large design headroom, and the use of components with established reliability result in a high MTBF. The unit meets the requirements of EN50155 for electronic equipment used on rolling stock. It is also suitable for transportation, mining, oilrigs, military and other harsh environments. The converter is manufactured at our plant under strict quality control. Customized versions are also available.

SPECIFICATIONS

Standard Input Voltages

24Vdc (17 - 34V)
 48Vdc (29 - 67V)
 72Vdc (43 - 101V)
 96Vdc (58 - 135V)
 110Vdc (66 - 154V)
 Consult factory for other voltages and ranges

Input Protection

Inrush current limiting
 Varistor
 Reverse polarity protection
 Internal safety fuse
 Lower voltage than specified minimum input will not damage unit

Isolation

1500Vdc input to chassis
 3000Vdc input to output
 1500Vdc output to chassis

Standards

Meets EN60950 and EN50155

Immunity

Meets criteria of EN50155 and EN50121-3-2 including:
 EN 61000-4-2 (ESD)
 EN61000-4-3 (RF Immunity)
 EN61000-4-4 (Fast transients)
 EN50155 (Surge)
 EN61000-4-6 (Conducted Imm.)
 EN50155 (Voltage Variations)

EMI

EN55022 Class B and EN50121-3-2 Conducted and radiated

Switching Frequency

55kHz \pm 3kHz

Standard Output Voltages

12V/40A, 24V/20A, 36V/13A,
 48V/10A or 110Vdc/4.5A
 Outputs are floating; either terminal can be grounded
 Consult factory for other outputs

Redundancy Diode

Not installed
 Available on custom versions

Line/Load Regulation

\pm 1% combined from zero load to full load on each output

Dynamic Response

Max 5% voltage deviation for 10% to 50% load step, with better than 1msec recovery time

Output Ripple/Noise

Less than 1% peak-to-peak or 0.2% RMS of the output voltage (20MHz BW)

Output Overload Protection

Rectangular current limiting with short-circuit protection (no hiccup)
 Thermal shutdown with automatic recovery in case of insufficient cooling

Output Overvoltage Protection

Second regulator loop completely stable and independent of main regulator loop

Terminal Block Pin-out.

OUTPUT				Spares for Options			GND	INPUT	
+	+	-	-	Not used	Not used	Not used	\perp	-	+
1	2	3	4	5	6	7	8	9	10

Efficiency

80 to 90% depending on input/output configuration

Operating Temperature Range

-40 to +70°C cold plate temperature for full specifications

Temperature Drift

0.03% per °C over operating temperature range

Cooling

Conduction cooling via base plate to customer chassis or heat-sink

Environmental Protection

Full encapsulation with thermally conductive silicon potting compound with UL94V-0 flammability rating

Shock/Vibration

IEC 61373 Cat 1 A&B

Humidity

5 - 95% non-condensing
 Contact factory for higher rating

MTBF

150,000 hours @ 45 °C
 Demonstrated MTBF is significantly higher

Indicators

None.

Control Input

None
 Enable or inhibit input as option

Alarm Output

None.
 Consult factory for options
 Available

Package/Dimensions (W x H x L)

P 500: 138 x 65 x 257 mm (5.5" x 2.6" x 10.1") including terminal block and flanges
 Mounting holes are clear

Weight

2.5 kg (5.5 lb)

Connections

10-pole barrier type terminal block

RoHS Compliance

Fully compliant

Warranty

Two years subject to application within good engineering practice

Enhancements to these general specifications and customizing can be accommodated upon request. Specifications are subject to change.



ANALYTIC SYSTEMS
 Power Conversion Solutions

8128 River Way, Delta B.C. V4G 1K5 Canada T. 604.946.9981 F. 604.946.9983 TF. 1.800.668.3884 (US/CANADA)

www.analyticssystem.com