


60W, Encapsulated DC/DC Converter for Railway and other Heavy Duty Applications RWY 60 Series

- ◆ Rugged, field-proven design
- ◆ Complete encapsulation
- ◆ Wide temperature range
- ◆ Full electronic protection
- ◆ Wide input ranges



The RWY 60 Series fully encapsulated, single output DC/DC converter uses a field-proven design to generate 60W output power. It is a mature product with a track-record in numerous applications. This converter is entirely potted with a thermally conductive MILgrade silicon rubber compound to ensure immunity to shock, vibration and humidity. It is conduction cooled via a base plate to a heat-sinking surface. Low component count, large design headroom, and the use of components with established reliability result in a high MTBF. The unit meets the requirements of EN50155 for electronic equipment used on rolling stock. The unit is also suitable for transportation, mining, oil rigs, military and other harsh environments. The RWY 60 is manufactured at our plant under strict quality control. Customized versions are also available.

SPECIFICATIONS

Standard Input Voltages

24Vdc (14.4 – 34V)
 36Vdc (22 – 51V)
 48Vdc (29 – 67V)
 72Vdc (43 – 101V)
 96Vdc (58 – 135V)
 110Vdc (66 – 154V)
 Other inputs upon request

Input Protection

Inrush current limiting
 Varistor
 Reverse polarity protection
 Internal safety fuse
 Lower voltage than specified minimum input will not damage unit

Isolation

1500Vdc input to chassis
 3000Vdc input to output
 1500Vdc output to chassis

Standards

Meets EN60950 and EN50155

Immunity

Meets criteria of EN50155 and EN50121-3-2 including EN 61000-4-2 (ESD)
 EN61000-4-3 (RF Immunity)
 EN61000-4-4 (Fast Transients)
 EN50155 (Surge)
 EN61000-4-6 (Conducted Imm.)
 EN50155 (Voltage Variations)

EMI

EN55022 Class B and EN50121-3-2 conducted and radiated

Switching Frequency

130kHz \pm 5kHz

Output Voltage

12V or 24V are standard. Output is floating, either terminal can be grounded
 Other outputs upon request

Redundancy Diode

None

Line/Load Regulation

+/- 1% combined from zero load to full load

Dynamic Response

Max 5% voltage deviation for 10% to 50% load step, with better than 1msec recovery time

Output Ripple/Noise

Less than 1% peak-to-peak or 0.2% RMS of the output voltage (20MHZ BW)

Output Overload Protection

Rectangular current limiting with hiccup type short-circuit protection
 Thermal shutdown with automatic recovery in case of insufficient cooling

Output Overvoltage Protection

Transzorb installed across the output

Efficiency

80 to 90% depending on input/output configuration

Operating Temperature Range

-40 to +70oC cold-plate temperature for full specification

Temperature Drift

0.03% per oC over operating temperature range

Cooling

Conduction cooling via base plate to customer heat-sink or chassis

Environmental Protection

Full encapsulation with thermally conductive silicon potting compound with UL94V-0 flammability rating

Shock/Vibration

IEC 61373 Cat 1 A&B

Humidity

5 – 95% non-condensing
 Contact factory for higher rating

MTBF

160,000 hours @ 45 oC
 Demonstrated MTBF is significantly higher

Indicators

None.
 Optional 'ON' LED available

Control Input

None

Alarm Output

None

Package/Dimensions (W x H x L)

P100: 58 x 54 x 181 mm (2.3" x 2.1" x 7.2") including terminal block and flanges
 Mounting holes are clear

Weight

0.6kg (1.4lb)

Connections

5-pole barrier-type terminal block with 3/8" spacing
 Cover can be provided upon request

RoHS Compliance

Fully compliant

Warranty

Two years subject to application within good engineering practice.

Enhancements to these general specifications and customizing can be accommodated upon request. Specifications are subject to change.



ANALYTIC SYSTEMS
 Power Conversion Solutions

8128 River Way, Delta B.C. V4G 1K5 Canada T. 604.946.9981 F. 604.946.9983 TF. 1.800.668.3884 (US/CANADA)

www.analyticssystem.com